



سن لوب لوبر كنتس اندستري ذ.م.م

SUNLUBE LUBRICANTS INDUSTRY LLC

TECHNICAL DATA SHEET

SYNTHETIC PETROL ENGINE OIL

Sunlube semi synthetic lubricants formulated from a blend of selected mineral oils, synthetic base stocks and high-quality additive technology for use in passenger cars and light truck gasoline engines and passenger car diesel engines under all operating conditions

BENEFITS:

- Blended with high quality of base stocks and additives which provide excellent oxidation resistance.
- Ensures good engine cleanliness, reducing particle accumulation in the motor via efficient dispersant
- Long-term wear protection of engine parts (distribution, ring, plunger and liner) increasing engine life

PERFORMANCE STANDARDS:

- API: SL/CF
- ILSAC: GF-5

TYPICAL PROPERTIES:

Properties	Unit	Test Method	
Grade	-		10W-30
Density @ 15°C	g/cm ³	ASTM D-4052	0.870
Kinematic Viscosity @ 40°C	mm ² /S	ASTM D-445	78.1
Kinematic Viscosity @ 100°C	mm ² /S	ASTM D-445	11.0
Viscosity Index	-	ASTM D-2270	130
Flash Point	°C	ASTM D-92	226
Pour Point	°C	ASTM D-97	-27
TBN	mg KOH/g	ASTM D-2896	7.5
CCS Viscosity	cP	ASTM D-5293	5200 (-25)

V.07-2025

PO.Box: 35746,Ras Al Khaimah,U.A.E

Tel: +971 7 2434 761
+971 7 2442 659

Email : inquiry@sunlube.ae

www.sunlube.ae

ص.ب: ٣٥٧٤٦، رأس الخيمة ا.ع.م

تليفون: +٩٧١ ٧٢٤٣٤٧٦١
+٩٧١ ٧٢٤٤٢٦٥٩