



سن لوب لوبر كنتس اندستري ذ.م.م

SUNLUBE LUBRICANTS INDUSTRY LLC

TECHNICAL DATA SHEET

MULTI PURPOSE GREASES

Sunlube Lithium Grease EP3 is a high-performance extreme pressure lithium lubricating grease that offers excellent protection against wear, rust, and corrosion. It has a wide range of operating temperatures between -20°C to 180°C and a long service life, making it ideal for automotive and industrial applications. It is recommended for multipurpose applications including high performance wheel bearing, chassis points, water pump bearing. They are pumpable and can be dispensed by and greasing system. EP-2 Grease is recommended for all normal grease application areas.

BENEFITS:

- Good mechanical stability.
- Acts as a protective layer on exposed parts
- Clings to bearing surfaces.
- Smooth texture.
- Excellent resistant to oxidation, rust and Corrosion.

PERFORMANCE STANDARDS:

- NLGI-3

TYPICAL PROPERTIES:

Properties	Unit	Test Method	
Grade	-		NLGI-3
Appearance	-	Visual	Buttery & smooth
Worked Penetration	-	ASTM D-217	240
Dropping Point, min.	°C	ASTM D-2265	190
Copper strip corrosion, 24 Hrs @100°C	-	ASTM D-4048	1B

V.07-2025